



**CUSTOMIZED
LENGTH
UPON
REQUEST**

Kanali 70 Linear LED

01 03 26

- Indoor recessed linear LED lighting fitting.
- Luminaire body made of extruded aluminium, polycarbonate diffuser and metal sheet end cups.
- Based on LED modules 350 mA.
- Correlated Color Temperature (CCT) 3000K, 4000K.
- Driver included.
- Dimmable options available.
- Luminaire life time > 50,000 hours at 80% of luminous flux.
- EMERGENCY VERSION UPON REQUEST.

CODE	4580 L	4581 L	4582 L	4583 L	4584 L
Frequency (Hz)	50/60	50/60	50/60	50/60	50/60
Main Voltage (V)	220-240	220-240	220-240	220-240	220-240
Source Power (W)	12,7	19	25,4	31,7	38,1
System Power (W)	13,3	20	26,7	33,3	40
Lumen Source (lm)	1830/1960	2750/2940	3660/3920	4580/4900	5490/5880
Lumen Luminaire (lm)	1470/1570	2200/2360	2930/3140	3670/3930	4400/4705
CCT (K)	3000/4000	3000/4000	3000/4000	3000/4000	3000/4000
Length (mm)	588	868	1148	1428	1708
Cut out (mm)	568 x 78	848 x 78	1128x 78	1408 x 78	1688 x 78
Weight (Kg)	1,1	1,4	1,7	2	2,3

CODE	4580 M	4581 M	4582 M	4583 M	4584 M
Frequency (Hz)	50/60	50/60	50/60	50/60	50/60
Main Voltage (V)	220-240	220-240	220-240	220-240	220-240
Source Power (W)	16	24	32	40	48
System Power (W)	21	25,2	33,6	42	50,4
Lumen Source (lm)	2690/2810	4030/4220	5380/5620	6720/7030	8070/8430
Lumen Luminaire (lm)	2150/2250	3225/3380	4310/4500	5380/5630	6460/6750
CCT (K)	3000/4000	3000/4000	3000/4000	3000/4000	3000/4000
Length (mm)	588	868	1148	1428	1708
Cut out (mm)	568 x 78	848 x 78	1128 x 78	1408 x 78	1688 x 78
Weight (Kg)	1,1	1,4	1,7	2	2,3

ACCESSORIES CODE	
4469	End Caps (pair)
4503	Linear connectors (pair)

FOR ACCESSORIES DETAILS SEE PAGE 155