



Brick EVO

581634.004 | Wall luminaires

Wall luminaires
4051859113836
LED
L 240, B 120, H 24



Flat surface-mounted LED fitting for illumination of wall related areas such as stairs, ramps or corridors. Housing made of corrosion-resistant die-cast aluminium, powder-coated. Diffuser with clear toughened glass. With compensation for drill hole deviations. Integral driver. With connecting terminal up to 1 x 3 x 1.5 mm², for max. 13 mm diameter mains cable.

Colour

Colour silver metallic

Dimensions

Length L 240 mm
Width B 120 mm
Height H 24 mm
Weight 710 g

Lamp

Lamp 1 LED
Colour temperature lamp 1 3000K
Colour rendering index (CRI) 1 80
Lifetime of lamp 1 combined 50000 h (L80/B10)

Lighting technology

Colour temperature 3.000 K
Rated luminous flux 180 lm
Glare evaluation UGR (4H 8H) 1 30,2
Beam angle 44° / 90° / 0° / 90°

Electrical

Control gear	Converter
Voltage	200 - 240 V / 50 Hz
Luminaires on B10A fuse	20
Luminaires on B16A fuse	30
Inrush current / inrush current duration	25.6 A / 3 μs
System power	10 W
Luminaire efficacy	18 lm/W

Approbations

Type of Protection	IP 65
Protection Class	I
Glow Wire Test	960°C - 30 seconds
Impact Protection	IK09 (10 Joule)
Safety marks	F-mark
ULOR	4,3 %
Trade mark	CE
CIE Flux Code / CEN Flux Code	49 80 95 96 100
Energy efficiency class LED	A+
Energy class of included lamp	A+