



Mega Tower

621097.0031.25 | Wall luminaires

Wall luminaires
4051859511281
LED
L 160, B 115, H 303



Attractive wall luminaire with innovative housing design and high-quality LED optics. Housing made of corrosion-resistant die-cast aluminium, seawater resistant powder-coated. With membrane valve as a standard to avoid condensed water. Luminaire head made of corrosion-resistant pressure die-cast aluminium, powder coated, with transparent cylinder (glass) and translucent anti-glare louvres. Fixing on the wall outside the gasketed volume, drill hole deviations can be compensated. Screwless luminaire fixing via RZB Gravalock® System.

Colour

Colour anthracite metallic

Dimensions

Length L 160 mm
Width B 115 mm
Height H 303 mm
Weight 3,1 kg

Lamp

Lamp 1 LED
Colour temperature lamp 1 3000K
Colour rendering index (CRI) 1 80
Colour consistency (McAdam) 1 3
Lifetime of lamp 1 combined 60000 h
Photobiological safety according to EN 62471 Risk group 1

Lighting technology

Colour temperature 3.000 K
Rated luminous flux 600 lm
Glare evaluation UGR (4H 8H) 1 23,6
Beam angle 180°

Electrical

Control gear	Converter
Voltage	220 - 240 V / 0 Hz, 50 - 60 Hz
Luminaires on B10A fuse	17
Luminaires on B16A fuse	27
Luminaires on C10A fuse	28
Luminaires on C16A fuse	45
Inrush current / inrush current duration	27 A / 250 µs
Ripple current / Flicker	3 %
System power	10 W
Luminaire efficacy	60 lm/W
Power factor	0,54

Approbations

Type of Protection	IP 65
Protection Class	I
Glow Wire Test	960°C - 30 seconds
Impact Protection	IK04 (0,50 Joule)
Safety marks	F-mark
ULOR	36,7 %
Trade mark	CE
CIE Flux Code / CEN Flux Code	7 31 69 63 100
Energy efficiency class LED	A++
Energy class of included lamp	A++