



Rondos Mini

911421.002.1 | Recessed projectors

Recessed projectors
4051859416425
LED
D 143, H 3, HEL 120



Recessed projectors Housing: die-cast aluminium, powder-coated. Rotation range: 356°; swivel range: ± 35°. Black plastic ring and recessed LED to prevent glare from the side. Optical assembly with lens made of plastic (polycarbonate) for the best homogeneous light distribution - can be changed without tools. UVA- and IR-free light. Installation without tools thanks to spring fastening system. Including separate LED converter with connecting cable 600 mm. High quality converter without flickering and stroboscopic effect. Through-wiring box (5 pole) available as accessory. The following accessories can be mounted without use of tools: interchangeable lenses, honeycomb louvre, clear and frosted diffusers, white interchangeable plastic ring.

Colour

Colour Traffic white, matt (RAL 9016)

Dimensions

Diameter D 143 mm
Height H 3 mm
Cut-out diameter DA 133 mm
Recess height HE 170 mm
Luminaire: recess height HEL 120 mm
Ceiling thickness S 1-20 mm
Dimensions L 156 x B 43 x H 30 mm
Weight 0,76 kg

Lamp

Lamp LED
Colour temperature 4000K
Colour rendering index (CRI) 85
Colour tolerance 2
Rated life 50000 h (L90/B10)
Photobiological safety according to EN 62471 Risk group 1

Lighting technology

Colour temperature 4.000 K
Rated luminous flux 2.550 lm
Glare evaluation UGR (4H 8H) 17,4
Beam angle 44°

Electrical

Control gear Converter
Voltage 220 - 240 V / 50 - 60 Hz
Luminaires on B10A fuse 21
Luminaires on B16A fuse 34
Luminaires on C10A fuse 35
Luminaires on C16A fuse 57
Inrush current / Inrush current duration 4.5 A / 65 µs
Ripple current / Flicker 4 %
System power 29 W
Luminaire efficacy 88 lm/W
Total harmonic distortion 20 %
Power factor 0,9

Approbations

Type of protection IP 20
Protection class II
Filament test 650°C - 30 seconds
Impact resistance IK06 (1 Joule)
Safety marks Einbauleuchte nicht bedecken!, F-mark
Ambient temperature min. -20 °C
Ambient temperature max. 27 °C
ULOR 0
Conformity mark CE, EAC
CIE Flux Code / CEN Flux Code 98 100 100 100 100
Energieeffizienzklasse 2019/2015 D
Non-maintained power mode Umgebungstemperatur / temperature ambiante => -20 °C ... + 27 °C

Rondos Mini

911421.002.1 | Recessed projectors



Accessories

982370.000	Diffuser D 74, H 3 Safety glass, clear.
982370.010	Diffuser D 74, H 3 Safety glass, satin finish
982371.003	Anti-glare honeycomb louvre D 74, H 3 Honeycomb louvre Mini
982369.003	Interchangeable optics D 82, H 55 Lens, narrow beam 18°
982369.013	Interchangeable optics D 82, H 55 Lens, medium beam 29°
982369.023	Interchangeable optics D 82, H 55 Lens, wide beam 44°
982421.002	Interchangeable plastic rings D 82, H 31 White plastic ring for lens
982368.003	Interchangeable optics D 82, H 55 Reflector, narrow beam 17°
982368.013	Interchangeable optics D 82, H 55 Reflector, medium beam 32°
982368.023	Interchangeable optics D 82, H 55 Reflector, wide beam 47°
982369.033	Interchangeable optics D 82, H 55 Lens, very wide beam 70°
982369.043	Interchangeable optics D 82, H 55 Lens with oval light distribution for corridor 28°/40°
982419.002	Interchangeable plastic rings D 82, H 20 White plastic ring for reflector
982368.033	Interchangeable optics D 82, H 55 Reflector, wide beam 62°
982703.002	Through-wiring box DALI L 98, B 55, H 28 Through-wiring box, 5 pole