



**CUSTOMIZED  
LENGTH  
UPON  
REQUEST**

# Astroline LED

01 03 26

- High output surface mounted or pendant Linear LED lighting system for continuous light.
- Body made of extruded aluminium powder coated white, black or grey.
- Polycarbonate diffuser.
- Single 3-step MacAdam ellipse, CRI >85.
- Based on LED modules of length 280mm.
- Seamless: no shadows between modules.
- Homogeneous light distribution.
- Highly efficient passive cooling system with large surface on top of luminaire for heat management.
- End-caps to be ordered separately.
- Suspension cables to be ordered separately.
- Driver included.
- Luminaire life time > 50,000 hours at 70% luminous flux.

CODE	3090	3091	3092	3093	3094
Frequency (Hz)	50/60	50/60	50/60	50/60	50/60
Main Voltage (V)	220-240	220-240	220-240	220-240	220-240
Source Power (W)	23,9	35,9	47,8	95,6	143,4
System Power (W)	25	37,7	50	100	151
Lumen Source (lm)	4000/4210	6000/6320	8000/8420	16000/16840	24000/25260
Lumen Luminaire (lm)	3200/3370	4800/5056	6400/6740	12800/13480	19200/20220
CCT (K)	3000/4000	3000/4000	3000/4000	3000/4000	3000/4000
Length (mm)	560	840	1120	2240	3360
Weight (Kg)	1,8	2,4	3,2	6,4	9,6

ACCESSORIES CODE	
4047	Suspension cable with power supply
4048	Suspension cable without power supply
3089	End Caps (pair)
4540	Linear connectors (pair)

FOR ACCESSORIES DETAILS SEE PAGE 155