

## RA 7



Modern, all-round downlight fixture.  
Driver must be ordered separately.

**Materials:** Korpus z odlewu aluminiowego malowanego poliestrowo, klosz OPAL z poliwęglanu.  
Oprawa charakteryzuje się możliwością montażu w sufitach podwieszanych o niewielkim prześwicie.

**Installation:** Into plaster cardboard and modular ceilings

**Accessories:** driver 500mA 20W

**Power:** 230 V

### ELECTRICAL DATA

Light source	LED
Luminaire power	4.6 W
Number of light sources	1
Light source power	4.6W
Voltage rating	220 ... 240 V
Light source included	Yes

### MECHANICAL DATA

Type of installation	For 600x600 ceiling
Mounting hole dimensions	60 mm
Housing material	Die cast aluminum

### INFORMATION

Colour	White
--------	-------

### BASIC DATA

Name	RA 7 4.6W 3000K White
EAN	8019163156433
Kod	IV251-200-21

### CERTIFICATES


Degree of protection (IP)	IP44
Impact resistance	IK07
Class of protection	III
Light source protection	Yes
CE	Yes
EAC	Yes

### LIGHT DATA

Light source luminous flux	540 lm
Luminaire luminous flux	378 lm
Light colour	White
Light distribution	DI
Beam angle	120 °
Colour temperature	3000K

### OPTICAL DATA

Diffuser colour	White
Diffuser material	Opal plastic



### DIMENSIONS

H [mm]	F [mm]	G [mm]
23	67	49

H = Height / Depth | F = Outer diameter | G = Inner diameter

### ACCESSORIES

---

## Electric element

---

Power supply 500 mA for RA4/RA7  
Pieces in set: 1

IV81-04031

Max can be connected:  
2 fittings of RA4L IV252-200-XX

---

IV81-04019

Max can be connected:  
4 fittings of RA4L IV252-200-XX  
8 fittings of RA4L IV252-210-XX  
3 fittings of RA7L IV251-200-XX

---