



CUSTOMIZED
LENGTH
UPON
REQUEST

Multiline LED

01

- Linear LED lighting for surface or suspended.
- Body made of extruded profile aluminium for passive cooling, with opal polycarbonate diffuser.
- Based on LED modules 350 mA, 3000K or 4000K.
- Base made from sheet metal painted in powder white.
- Polycarbonate end cups included.
- Homogeneous light distribution on whole beam.
- Suspension to be ordered separately.
- Luminaire life time > 50,000 hours at 80%.

CODE	3500 M	3510 M	3520 M	3530 M	3540 M
Frequency (Hz)	50/60	50/60	50/60	50/60	50/60
Main Voltage (V)	220-240	220-240	220-240	220-240	220-240
Source Power (W)	16	24	32	40	48
System Power (W)	21	25,2	33,6	42	50,4
Lumen Source (lm)	2690/2810	4030/4220	5380/5620	6720/7030	8070/8430
Lumen Luminaire (lm)	2150/2250	3225/3380	4310/4500	5380/5630	6460/6750
CCT (K)	3000/4000	3000/4000	3000/4000	3000/4000	3000/4000
Length (mm)	580	900	1180	1480	1700
Weight (Kg)	1,1	1,4	1,7	2	2,3

CODE	3500 L	3510 L	3520 L	3530 L	3540 L
Frequency (Hz)	50/60	50/60	50/60	50/60	50/60
Main Voltage (V)	220-240	220-240	220-240	220-240	220-240
Source Power (W)	12,7	19	25,4	31,7	38,1
System Power (W)	13,3	20	26,7	33,3	40
Lumen Source (lm)	1830/1960	2750/2940	3660/3920	4580/4900	5490/5880
Lumen Luminaire (lm)	1470/1570	2200/2360	2930/3140	3670/3930	4400/4710
CCT (K)	3000/4000	3000/4000	3000/4000	3000/4000	3000/4000
Length (mm)	580	900	1180	1480	1700
Weight (Kg)	1,1	1,4	1,7	2	2,3

ACCESSORIES CODE

4047	Suspension cable with power supply
4048	Suspension cable without power supply

FOR ACCESSORIES DETAILS SEE PAGE 155