


Douala

312257.000.1.76 | Ceiling and wall luminaires

Ceiling and wall luminaires
4051859373230
LED
D 400, H 102



Decorative round surface-mounted luminaire. Base: brushed stainless steel. Mouth-blown, 3-layer opal glass, satin finish. With decorative screen, aluminium. Patented spring fastening system. Suitable for Ceiling mounting, Wall (surface). For recessed ceiling and recessed wall applications the recess housing must be ordered separately.

Colour

Colour stainless steel, brushed

Dimensions

Diameter D 400 mm
Height H 102 mm
Weight 4,85 kg

Lamp

Lamp LED
Colour temperature 4000K
Colour rendering index (CRI) 83
Colour tolerance 3
Rated life 50000 h (L70/B10)
Photobiological safety according to EN 62471 Risk group 1

Lighting technology

Colour temperature 4.000 K
Rated luminous flux 2.800 lm
Glare evaluation UGR (4H 8H) 1 21,9
Beam angle 130°

Electrical

Control gear	AC power, DALI dimmable
Voltage	230 V / 50 - 60 Hz
Luminaires on B10A fuse	65
Luminaires on B16A fuse	104
Luminaires on C10A fuse	65
Luminaires on C16A fuse	104
Inrush current / Inrush current duration	0.17 A
System power	31 W
Luminaire efficacy	91 lm/W

Approbations

Type of protection	IP 40
Protection class	I
Filament test	960°C - 30 seconds
Impact resistance	IK02 (0,20 Joule)
Safety marks	F-mark
ULOR	16,7 %
Conformity mark	CE, EAC
CIE Flux Code / CEN Flux Code	40 70 89 83 100
Energieeffizienzklasse 2019/2015	E

Accessories

981763.000	Accessories D 426, H 90, HE 90 for luminaires D 400, Cut out DA 410 mm
------------	---