



Perfetto Puro



Modern floodlight designed especially for LED COB light sources. It can rotate up to 350° with respect to the vertical axis and pivot up to 90° upwards.

Materials: body and component compartment in polyester painted die-cast aluminum. Reflectors in polycarbonate with mirror finish

Installation: for electrical track

Accessories: reflector for beam angle regulation

Power: 230 V

ELECTRICAL DATA

Light source	LED
Number of light sources	1
Voltage rating	220 ... 240 V
Light source included	Yes

MECHANICAL DATA

Type of installation	for tracks
Housing material	Die cast aluminum

INFORMATION

Rotated model	Yes
---------------	-----

CERTIFICATES

Degree of protection (IP)	IP20
Class of protection	I
Energy class	A+
CE	Yes
ENEC	Yes

LIGHT DATA

Color rendering index	85
Light distribution	DI
Beam angle	30 °
Light output degradation	B10
Lifetime	> 50000 h

AVAILABLE VARIANTS

Product code	Light source power [W]	Luminaire luminous flux [lm]	Colour temperature	Colour
IV770-061-16	1×32	3916	3000K	Black
IV770-061-21	1×32	3916	3000K	White
IV770-061-52	1×32	3916	3000K	Grey
IV770-061A-16	1×32	4005	4000K	Black
IV770-061A-21	1×32	4005	4000K	White
IV770-061A-52	1×32	4005	4000K	Grey
IV770-261-16	1×37	4450	3000K	Black
IV770-261-21	1×37	4450	3000K	White
IV770-261-52	1×37	4450	3000K	Grey
IV770-261A-16	1×37	4583	4000K	Black
IV770-261A-21	1×37	4583	4000K	White
IV770-261A-52	1×37	4583	4000K	Grey

DIMENSIONS

L [mm]	H [mm]	F [mm]
92	110	84

L = Length | H = Height / Depth | F = Outer diameter

