



Calido Clickbeam Midi

742130.003.1 | Surface mounted projector

Surface mounted projectors
4051859364429
LED
D 65, H 164



LED surface-mounted projector with modern cylindrical design with no visible cooling ribs. Housing: extruded aluminium profile, powder-coated. Cover and lever arm made of plastic. Rotation range: 356°. Swivel range: 90°. Heat resistant plastic ring black. Hybrid optical system with polycarbonate lens and reflector in faceted aluminium for particularly homogeneous lighting. Special Click Beam lens suitable for different beam angles. Adjustable lens position by means of push mechanism to adjust the beam angle. Black front ring to prevent glare from the side UVA- and IR-free light. With multi adaptor for 3-circuit tracks 230 V. Suitable for Track on ceiling. Converter integrated in the luminaire housing. The following accessories can be mounted without use of tools: honeycomb louvre.

Colour

Colour deep black, matt (RAL 9005)

Dimensions

Diameter D 65 mm
Height H 164 mm
Weight 490 g

Lamp

Lamp 1 LED
Colour temperature lamp 1 4000K
Colour rendering index (CRI) 1 80
Colour consistency (McAdam) 1 3
Lifetime of lamp 1 combined 50000 h (L70/B50)
Photobiological safety according to EN 62471 Risk group 1

Lighting technology

Colour temperature 4.000 K
Rated luminous flux 1.950 lm
Glare evaluation UGR (4H 8H) 1 20,6
Beam angle 22°
Colour temperature 2 4.000 K
Rated luminous flux 2 2.000 lm
Glare evaluation UGR (4H 8H) 2 22,3
Beam angle Down 2 38°

Electrical

Control gear Converter
Voltage 220 - 240 V / 50 - 60 Hz
Luminaires on B10A fuse 7
Luminaires on B16A fuse 12
Luminaires on C10A fuse 15
Luminaires on C16A fuse 25
Inrush current / inrush current duration 6,4 A / 16 µs
System power 25 W
Luminaire efficacy 78 lm/W
System power 2 25 W
Luminaire efficacy 2 80 lm/W
Power factor 0,9

Approbations

Type of Protection IP 20
Protection Class II
Glow Wire Test 850°C - 30 seconds
Impact Protection IK03 (0,35 Joule)
Safety marks F-mark
ULOR 0
Trade mark CE
CIE Flux Code / CEN Flux Code 93 98 100 100 100
Energy efficiency class LED A++
Energy class of included lamp A++

Calido Clickbeam Midi

742130.003.1 | Surface mounted projector



Accessories

982544.003

Anti-glare honeycomb louvre
D 55, H 4
Anti-glare honeycomb louvre
Calido Midi