


# Deecos S Mini

742027.002.1 | Surface mounted projector

Surface mounted projectors  
4051859400455  
LED  
D 87, H 214



LED surface-mounted projector in modern design with no visible cooling ribs. Housing: die-cast aluminium, powder-coated. Rotation range: 356°. Swivel range: 90°. Black plastic ring and recessed LED to prevent glare from the side. Optical assembly with lens made of plastic (polycarbonate) for the best homogeneous light distribution - can be changed without tools. High quality converter without flickering and stroboscopic effect. With multi adaptor for 3-circuit tracks 230 V. Suitable for Track on ceiling, Wall track. The following accessories can be mounted without use of tools: interchangeable lenses, decorative glasses, honeycomb louvre, clear and frosted diffusers, white interchangeable plastic ring.

## Colour

Colour Traffic white, matt (RAL 9016)

## Dimensions

Diameter D 87 mm  
Height H 214 mm  
Weight 1,15 kg

## Lamp

Lamp LED  
Colour temperature 4000K  
Colour rendering index (CRI) 85  
Colour tolerance 2  
Rated life 50000 h (L90/B10)  
Photobiological safety according to EN 62471 Risk group 1

## Lighting technology

Colour temperature 4.000 K  
Rated luminous flux 2.550 lm  
Glare evaluation UGR (4H 8H) 1 17,4  
Beam angle 44°

## Electrical

Control gear	Converter
Voltage	220 - 240 V / 50 - 60 Hz
Luminaires on B10A fuse	15
Luminaires on B16A fuse	24
Luminaires on C10A fuse	24
Luminaires on C16A fuse	40
Inrush current / Inrush current duration	22 A / 260 µs
Ripple current / Flicker	4 %
System power	29 W
Luminaire efficacy	88 lm/W
Total harmonic distortion	10 %
Power factor	0,9

## Approbations

Type of protection	IP 20
Protection class	I
Filament test	650°C - 30 seconds
Impact resistance	IK06 (1 Joule)
Safety marks	F-mark
ULOR	0
Conformity mark	CE, EAC
CIE Flux Code / CEN Flux Code	98 100 100 100 100
Energieeffizienzklasse 2019/2015	D

# Deecos S Mini

742027.002.1 | Surface mounted projector



## Accessories

982370.000	Diffuser D 74, H 3 Safety glass, clear.
982370.010	Diffuser D 74, H 3 Safety glass, satin finish
982371.003	Anti-glare honeycomb louvre D 74, H 3 Honeycomb louvre Mini
982369.003	Interchangeable optics D 82, H 55 Lens, narrow beam 18°
982369.013	Interchangeable optics D 82, H 55 Lens, medium beam 29°
982369.023	Interchangeable optics D 82, H 55 Lens, wide beam 44°
982421.002	Interchangeable plastic rings D 82, H 31 White plastic ring for lens
982368.003	Interchangeable optics D 82, H 55 Reflector, narrow beam 17°
982368.013	Interchangeable optics D 82, H 55 Reflector, medium beam 32°
982368.023	Interchangeable optics D 82, H 55 Reflector, wide beam 47°
982369.033	Interchangeable optics D 82, H 55 Lens, very wide beam 70°
982369.043	Interchangeable optics D 82, H 55 Lens with oval light distribution for corridor 28°/40°
982419.002	Interchangeable plastic rings D 82, H 20 White plastic ring for reflector
982368.033	Interchangeable optics D 82, H 55 Reflector, wide beam 62°
982647.002	Decorative glasses D 87, H 41 Diffuser: mouth-blown opal glass, satin finish with bayonet lock.
982648.002	Decorative glasses D 87, H 76 Diffuser: mouth-blown opal glass, satin finish with bayonet lock.