



VIP G/K LED



Lighting luminaire from the family VIP, adapted for mounting into plaster-cardboard ceiling. The appropriate joints (linear and T-joint) allow to connect the luminaires in a straight line or to create the 90° angle. Light source: LED

Materials: Powder painted aluminum profile (standard color: grey), OPAL diffuser.

Installation: Into plaster-cardboard ceiling with appropriate mounting brackets.

Accessories: Joints (linear or 90°), end caps.

Power: 230 V

ELECTRICAL DATA

Light source	LED
Number of light sources	1
Type of equipment	AC
Voltage rating	220 ... 240 V
Through-wiring	Yes
Light source included	Yes

MECHANICAL DATA

Type of installation	Recessed
Housing material	Aluminum
Designed for light-line	Yes

INFORMATION

Colour	Grey
Operating temperature range	-15 ... 40 °C
Info	OPAL

CERTIFICATES

Degree of protection (IP)	IP20
Degree of protection (IP) / top/	IP20
Class of protection	I
Energy class	A+
CE	Yes
PZH	Yes
EAC	Yes

LIGHT DATA

Light colour	White
Color rendering index	84
Light distribution	Wide beam
Light distribution	DI
Class of luminaire	I
Light output degradation	B10
Lumen maintenance	L80
Lifetime	> 72000 h
MacAdam	SDCM 3
Lamp Lumen Maintenance Factor (after 60 000h)	85 %

OPTICAL DATA

Louver/ shutter	OPAL
Diffuser colour	White
Diffuser material	Opal/mat plastic
Reflector	High gloss



AVAILABLE VARIANTS

Product code	Luminaire power [W]	Luminaire luminous flux [lm]	Luminaire's luminous efficacy [lm/W]	Colour temperature	Weight [kg]
PX4070301 BJ001.2211.830.A000	17	1380	81	3000K	1.50

AVAILABE VARIANTS

Product code	Luminaire power [W]	Luminaire luminous flux [lm]	Luminaire's luminous efficacy [lm/W]	Colour temperature	Weight [kg]
PX4070308 BJ001.2211.840.A000	17	1410	83	4000K	1.50
PX4070315 BJ002.2211.830.A000	24	2070	86	3000K	2.20
PX4070322 BJ002.2211.840.A000	24	2110	88	4000K	2.20
PX4070329 BJ003.2211.830.A000	31	2760	89	3000K	2.80
PX4070336 BJ003.2211.840.A000	31	2820	91	4000K	2.80
PX4070343 BJ004.2211.830.A000	38	3450	91	3000K	3.40
PX4070350 BJ004.2211.840.A000	38	3520	93	4000K	3.40
PX4070357 BJ005.2211.830.A000	44	4140	94	3000K	4.10
PX4070364 BJ005.2211.840.A000	44	4220	96	4000K	4.10
PX4070371 BJ006.2211.830.A000	52	4830	93	3000K	4.80
PX4070378 BJ006.2211.840.A000	52	4930	95	4000K	4.80

DIMENSIONS



Product code	L [mm]	W [mm]	H [mm]	C [mm]	D [mm]
PX4070301 BJ001.2211.830.A000	585	86	65	590	70
PX4070308 BJ001.2211.840.A000	585	86	65	590	70
PX4070315 BJ002.2211.830.A000	875	86	65	880	70
PX4070322 BJ002.2211.840.A000	875	86	65	880	70
PX4070329 BJ003.2211.830.A000	1165	86	65	1170	70
PX4070336 BJ003.2211.840.A000	1165	86	65	1170	70
PX4070343 BJ004.2211.830.A000	1455	86	65	1460	70
PX4070350 BJ004.2211.840.A000	1455	86	65	1460	70
PX4070357 BJ005.2211.830.A000	1745	86	65	1750	70
PX4070364 BJ005.2211.840.A000	1745	86	65	1750	70
PX4070371 BJ006.2211.830.A000	2035	86	65	2040	70
PX4070378 BJ006.2211.840.A000	2035	86	65	2040	70

L = Length | W = Width | H = Height / Depth | C = Installation length | D = Installation width

ACCESSORIES

Structural element



VIP G/K End cap

PX0990122
FE014.22.0002

OPAL

Grey
