



CEILING AND SUSPENDED



9171 S



9171 C



Cylinder Asterion LED



- Ceiling mounted or suspended interior light fixture.
- Body made of aluminium, powder painted, with clear protection glass.
- Led Bridgelux V13.
- CRI 90 upon request.
- Alunova LED reflector.
- Passive cooling (no moving parts).
- LED driver included .
- Luminaire lifetime > 50,000 hours at 70% luminous flux.

| CODE | 9171C 9171S | 9172C 9172S | 9173C 9173S | 9175C 9175S | 9176C 9176S | 9177C 9177S |
|----------------------|----------------|----------------|----------------|----------------|----------------|----------------|
| Frequency (Hz) | 50/60 | 50/60 | 50/60 | 50/60 | 50/60 | 50/60 |
| Main Voltage (V) | 220-240 | 220-240 | 220-240 | 220-240 | 220-240 | 220-240 |
| Source Power (W) | 17,5 | 17,5 | 17,5 | 25,3 | 25,3 | 25,3 |
| System Power (W) | 18,4 | 18,4 | 18,4 | 26,6 | 26,6 | 26,6 |
| Lumen Source (lm) | 2658/2764 | 2658/2764 | 2658/2764 | 3600/3744 | 3600/3744 | 3600/3744 |
| Lumen Luminaire (lm) | 2126/2211 | 2126/2211 | 2126/2211 | 2880/2995 | 2880/2995 | 2880/2995 |
| CCT (K) | 3000/4000 | 3000/4000 | 3000/4000 | 3000/4000 | 3000/4000 | 3000/4000 |
| Beams | 16° | 24° | 41° | 16° | 24° | 41° |
| CRI | ≥ 80 | ≥ 80 | ≥ 80 | ≥ 80 | ≥ 80 | ≥ 80 |
| Weight (Kg) | 3,2 | 3,2 | 3,2 | 3,2 | 3,2 | 3,2 |

