


GSUN S

672218.002.1 | Self-contained safety luminaires



Ceiling and wall luminaires
4051859397205
LED
L 327, B 45, H 237



Housing: aluminium extrusion profile. With universal mounting kit for ceiling and wall surface mounting. 3 pictogram legend foils and 1 white foil included. Automatic self-test as standard feature. Lamp included.

Emergency lighting

Emergency luminaire	with integrated battery (self-contained)
Battery Option	NiCd
Operating mode	Maintained power mode/Non-maintained power mode
Monitoring	Automatic self-test
Duration time	1 h, 3 h, 8 h
Type of Installation	Wall (surface), Ceiling (surface)
Viewing Distance	32 m

Colour

Colour	white
--------	-------

Dimensions

Length L	327 mm
Width B	45 mm
Height H	237 mm
Weight	1,35 kg

Lamp

Lamp 1	LED
Colour temperature lamp 1	4000K

Electrical

Control gear	Converter
Voltage	220 - 240 V / 50 - 60 Hz
Luminaires on B10A fuse	5
Luminaires on B16A fuse	10
Luminaires on C10A fuse	15
Luminaires on C16A fuse	20
System power	5,5 W

Approbations

Type of Protection	IP 30
Protection Class	I
Glow Wire Test	650°C - 30 seconds
Impact Protection	IK03 (0,35 Joule)
Safety marks	F-mark
Trade mark	CE
Energy efficiency class conventional lamp	Mark not necessary
Energy efficiency class LED	Mark not necessary
Energy class of included lamp	A

GSUN S

672218.002.1 | Self-contained safety luminaires



Accessories

981777.012.1	Pendant tube set LP 500 for standard variants
981780.002.1	Mounting sets L 238, B 40, H 32 Mounting kit for chains/cable suspensions
981884.002.1	Mounting frame for recessed ceiling mounting L 406, B 68, H 1, HE 75, LA 370, BA 52, HE 75 for Viewing distance 32 m
981797.002.1	Wall bracket L 338, B 46, H 90 for Viewing distance 32 m
991129.03	Escape route motif foils 4 motif foils (1 each of 3113, 3114, 3115, 3116) for Viewing distance 32 m