


Lavano Wing

451197.000.1 | Pendant luminaires



Pendant luminaires
4051859173533
LED
L 1140, B 150, H 180



Linear pendant luminaire in elegant design. Extruded aluminium profile base, lacquered. End caps aluminium, painted. Diffuser (tapering at the sides): plastic (PMMA), opal, allows for brilliant glittering light. The conical diffusers generate a brightly sparkling amount of direct light along the contour of the ellipse. Suitable for Pendant. 2-point steel cable suspension, steplessly adjustable. Special lengths available on request.

Colour

Colour anodised aluminium

Dimensions

Length L 1.140 mm
Width B 150 mm
Height H 180 mm
Suspension length LP 500-1200 mm
Weight 3,74 kg

Lamp

Lamp LED
Colour temperature 3000K
Colour rendering index (CRI) 80
Colour tolerance 3
Rated life 50000 h (L90/B10)
Photobiological safety according to EN 62471 Risk group 1

Lighting technology

Colour temperature 3.000 K
Rated luminous flux 5.700 lm
Glare evaluation UGR (4H 8H) 1 20,7
Beam angle 180° / 109°

Electrical

Control gear	Constant voltage supply
Voltage	220 - 240 V / 50 - 60 Hz
Luminaires on B10A fuse	5
Luminaires on B16A fuse	9
Luminaires on C10A fuse	9
Luminaires on C16A fuse	15
Inrush current / Inrush current duration	62 A / 220 μs
Ripple current / Flicker	10 %
System power	47 W
Luminaire efficacy	122 lm/W
Total harmonic distortion	10 %
Power factor	0,98

Approbations

Type of protection	IP 40
Note: Type of Protection	IP 40
Protection class	I
Filament test	650°C - 30 seconds
Impact resistance	IK03 (0,35 Joule)
Safety marks	F-mark
ULOR	58,5 %
Conformity mark	CE, EAC
CIE Flux Code / CEN Flux Code	39 66 82 42 100
Energieeffizienzklasse 2019/2015	E