



**CUSTOMIZED LENGTH UPON REQUEST**

# Ena LED



- Linear LED lighting fixture surface mounted or suspended.
- Body made of extruded aluminium with PC opal cover, polyester powder white, black or grey.
- Intergrated Driver.
- Correlated Color Temperature (CCT) 3000K, 4000K,(single 3-step MacAdam ellipse), CRI >85.
- Based on LED modules of length 280mm.
- Homogeneous light distribution.
- Dimming DSI or Dali available on request.
- Luminaire life time > 50,000 hours at 70% luminous flux.
- Emergency version only for codes 3652 and 3653.
- End caps included.

CODE	3650	3651	3652	3653
Frequency (Hz)	50/60	50/60	50/60	50/60
Main Voltage (V)	220-240	220-240	220-240	220-240
Source Power (w)	12,7	19	25,4	31,7
System Power (w)	13,3	20	26,7	33,3
Lumen Source (lm)	1830/1960	2750/2940	3660/3920	4580/4900
Lumen Luminaire (lm)	1470/1570	2200/2360	2930/3140	3670/3930
CCT (K)	3000/4000	3000/4000	3000/4000	3000/4000
Length (mm)	565	845	1125	1405
Weight (Kg)	2	3	3,8	4,8

CODE	3650 M	3651 M	3652 M	3653 M
Frequency (Hz)	50/60	50/60	50/60	50/60
Main Voltage (V)	220-240	220-240	220-240	220-240
Source Power (w)	16	24	32	40
System Power (w)	21	25,2	33,6	42
Lumen Source (lm)	2690/2810	4030/4220	5380/5620	6720/7030
Lumen Luminaire (lm)	2150/2250	3225/3380	4310/4500	5380/5630
CCT (K)	3000/4000	3000/4000	3000/4000	3000/4000
Length (mm)	565	845	1125	1405
Weight (Kg)	2	3	3,8	4,8

ACCESSORIES CODE	
4047	Suspension cable with power supply
4048	Suspension cable without power supply

FOR ACCESSORIES DETAILS SEE PAGE 155