



## Dynamic LED

01 03

- Indoor ceiling recessed fully adjustable LED downlight.
- All elements made of diecast aluminium electrostatically polyester powder coated.
- Tilttable : 35° - Rotation 360°.
- Extruded aluminium passive cooling system black anodized for optimal heat dissipation.
- With Bridgelux V15 LEDs.
- Clear protection glass. Stainless steel springs.
- CRI 90 available upon request.
- Luminaire life time > 50,000 hours at 70% luminous flux.
- LED driver to be ordered separately.
- EMERGENCY VERSION UPON REQUEST.

CODE	2101	2101	2101	2101
Max Input (mA)	500 DC	700 DC	900 DC	1050 DC
Source Power (W)	17,5	25,2	33,4	39,5
Lumen Source (lm)	2366/2511	3178/3372	3905/4144	4450/4722
Lumen Luminaire (lm)	1893/2009	2543/2698	3124/3315	3560/3778
CCT (K)	3000/4000	3000/4000	3000/4000	3000/4000
Beams	25°, 60°	25°, 60°	25°, 60°	25°, 60°
CRI	≥ 80	≥ 80	≥ 80	≥ 80
Cut Out Ø (mm)	145	145	145	145
Weight (Kg)	0,72	0,72	0,72	0,72