


# Less is more 27

## 312208.002.1 | LED linear systems

Pendant luminaires  
4051859232735  
LED  
L 1012, B 28, H 38



Pendant luminaire with slim design. Housing: extruded aluminium profile, powder-coated. End cap aluminium powder-coated. Diffuser made of non-yellowing plastic (PMMA), opal. Direct 60%, indirect 40% light emission. Suitable for Pendant. 2-point steel cable suspension, steplessly adjustable. Special lengths available on request. Converter integrated in the canopy.

### Colour

Colour white

### Dimensions

Length L 1.012 mm  
Width B 28 mm  
Height H 38 mm  
Suspension length LP 100-1500 mm  
Weight 1,7 kg

### Lamp

Lamp LED  
Colour temperature 4000K  
Colour rendering index (CRI) 82  
Colour tolerance 3  
Rated life 60000 h (L80/B10)  
Photobiological safety according to EN 62471 Risk group 1

### Lighting technology

Colour temperature 4.000 K  
Rated luminous flux 2.700 lm  
Glare evaluation UGR (4H 8H) 1 25,2  
Beam angle 108° / 112°

### Electrical

Control gear	Converter
Control gear	Converter
Voltage	220 - 240 V / 50 - 60 Hz
Luminaires on B10A fuse	11
Luminaires on B16A fuse	18
Luminaires on C10A fuse	19
Luminaires on C16A fuse	31
Inrush current / Inrush current duration	24 A / 275 µs
Ripple current / Flicker	1,6 %
System power	34 W
Luminaire efficacy	80 lm/W
Power factor	0,95

### Approbations

Type of protection	IP 20
Protection class	I
Filament test	650°C - 30 seconds
Safety marks	F-mark
ULOR	34,8 %
Conformity mark	CE, EAC
CIE Flux Code / CEN Flux Code	48 79 96 65 100
Energieeffizienzklasse 2019/2015	E