


Triade LED

751142.002.1 | Surface mounted projector

Surface mounted projectors
4051859093985
LED
L 1160, B 89, H 178



LED spotlight for surface / track mounting in geometrical design for indoor applications. For general and wall lighting. Housing: extruded aluminium profile, powder-coated. Swivel range: 90°. Diffuser: plastic (polycarbonate), opal. Homogeneous and smooth light distribution. With multi adaptor for 3-circuit tracks 230 V. Suitable for Track on ceiling. Integral driver.

Colour

Colour Traffic white, matt (RAL 9016)

Dimensions

Length L 1.160 mm
Width B 89 mm
Height H 178 mm
Weight 2,89 kg

Lamp

Lamp LED
Colour temperature 4000K
Colour rendering index (CRI) 80
Colour tolerance 4
Rated life 50000 h (L70/B10)
Photobiological safety according to EN 62471 Risk group 1

Lighting technology

Colour temperature 4.000 K
Rated luminous flux 5.400 lm
Glare evaluation UGR (4H 8H) 1 26,1
Beam angle 87° / 99°

Electrical

Control gear	Converter
Voltage	220 - 240 V / 50 - 60 Hz
Luminaires on B10A fuse	17
Luminaires on B16A fuse	28
Inrush current / Inrush current duration	53 A / 220 µs
System power	60 W
Luminaire efficacy	90 lm/W
Power factor	0,98

Approbations

Type of protection	IP 20
Protection class	I
Filament test	650°C - 30 seconds
Impact resistance	IK02 (0,20 Joule)
Safety marks	F-mark
ULOR	0
Conformity mark	CE, EAC
CIE Flux Code / CEN Flux Code	53 83 97 100 100
Energieeffizienzklasse 2019/2015	E