



- Aluminium profile body.
- Mains voltage: 220-240V / 50-60Hz.
- Clever thermal design.
- 1-10V and DALI dimming options available upon request.
- 1x20° half batwing and 1x30° half batwing reflector options available.
- Basic colours: white, black, silver, antracite dark gray and special color options available upon request.
- Over 135lm/W efficiency.
- Emergency kit system can be integrated.
- Continuous line installation possible.

- Alüminyum profil gövde.
- 220-240V / 50-60Hz enerji giriřli.
- Akıllı soğutma tasarımı.
- 1-10V ve DALI dim seçenekleri bulunmaktadır.
- 1x20° ve 1x30° tek asimetrik açı seçenekleri mevcuttur.
- Standart renkler: beyaz, siyah, gri, antrasit koyu gri ve isteğe bağılı özel renk seçenekleri mevcuttur.
- 135lm/W'in üzerinde verimlilik.
- Acil aydınlatma kit sistemi uygulanabilir.
- Lineer kesintisiz montaj sistemine uyumlu.

### Systema / I02.LL.19460

LED	SMD LED	
Led Power / Led Gücü	49W	
System Power / Sistem Gücü	52W	
Lumen Output from Fixture / Armatür Çıkış Lümeni CRI>80	2700K	6505
	3000K	6705
	3500K	6915
	4000K	7127
	5000K	7340
Length / Uzunluk (A)	1510mm	
Ceiling Cutout Dimension / Tavan Delik Ölçüsü	X	
Mains Switch Dim Option / 220V Anahtar Dim Opsiyonu	X	
1-10V Dimming Option / 1-10V Dim Seçeneđi	✓	
Dali Dimming Option / Dali Dim Seçeneđi	✓	

