


Flat Polymero IP44

221154.002.3.76 | Ceiling and wall luminaires

Ceiling and wall luminaires
4051859183747
LED
D 420, H 150



Decorative round surface-mounted luminaire for indoor and outdoor use. Base: plastic. Diffuser made of non-yellowing plastic (PMMA), opal. Diffuser fastening: spring system. Suitable for Ceiling mounting, Wall (surface). IP 43 ceiling mounting, IP 44 wall mounting.

Colour

Colour white

Dimensions

Diameter D 420 mm
Height H 150 mm
Weight 1,78 kg

Lamp

Lamp LED
Colour temperature 4000K
Colour rendering index (CRI) 83
Colour tolerance 3
Rated life 50000 h (L70/B10)
Photobiological safety according to EN 62471 Risk group 1

Lighting technology

Colour temperature 4.000 K
Rated luminous flux 2.000 lm
Glare evaluation UGR (4H 8H) 1 19,7
Beam angle 118°

Electrical

Control gear	AC power, DALI dimmable
Voltage	220 - 240 V / 50 - 60 Hz
Luminaires on B10A fuse	87
Luminaires on B16A fuse	139
Luminaires on C10A fuse	87
Luminaires on C16A fuse	139
Inrush current / Inrush current duration	0,1 A / 10000 µs
System power	21 W
Luminaire efficacy	96 lm/W

Approbations

Type of protection	IP 43
Note: Type of Protection	IP 43 ceiling mounting, IP 44 wall mounting
Protection class	I
Filament test	650°C - 30 seconds
Impact resistance	IK02 (0,20 Joule)
Safety marks	F-mark
ULOR	11,6 %
Conformity mark	CE, EAC
CIE Flux Code / CEN Flux Code	41 70 89 88 100
Energieeffizienzklasse 2019/2015	E