


Scapha

311990.004.1 | Pendant luminaires

Pendant luminaires
4051859155201
LED
L 714, B 134, H 62



Pendant luminaire with elliptical shape. Base: aluminium, powder-coated. Canopy and glass fixture steel powder-coated. Handmade concave glass, matt finish on the outside, painted white on the inside. Uniform and glare-free illumination of the small boat shaped corpus by specially adapted LED panel boards. Suitable for Pendant. 2-point steel cable suspension, steplessly adjustable. Special lengths available on request.

Colour

Colour silver metallic

Dimensions

Length L 714 mm
Width B 134 mm
Height H 62,5 mm
Suspension length LP 500-1200 mm
Weight 3,66 kg

Lamp

Lamp LED
Colour temperature 4000K
Colour rendering index (CRI) 80
Colour tolerance 3
Rated life 50000 h (L80/B10)

Lighting technology

Colour temperature 4.000 K
Rated luminous flux 2.500 lm
Glare evaluation UGR (4H 8H) 1 25,3
Beam angle 162° / 113°

Electrical

Control gear	Converter
Voltage	220 - 240 V / 0 Hz, 50 - 60 Hz
Luminaires on B10A fuse	31
Luminaires on B16A fuse	50
Luminaires on C10A fuse	52
Luminaires on C16A fuse	85
Inrush current / Inrush current duration	5 A / 50 µs
Ripple current / Flicker	3 %
System power	35 W
Luminaire efficacy	72 lm/W
Power factor	0,95

Approbations

Type of protection	IP 20
Protection class	I
Filament test	960°C - 30 seconds
Impact resistance	IK00 (no protection)
Safety marks	F-mark
ULOR	10,9 %
Conformity mark	CE, EAC
CIE Flux Code / CEN Flux Code	37 66 86 89 100
Energieeffizienzklasse 2019/2015	E