



## 401701 ECLIPSE MINI ROUND Designed by PAOLO VILLA

Round wall surface-mounted luminaire creating a **diffused and discrete light through the fixture perimeter** on the wall. Fixture for outdoor installation on a wall. Phospho-chromatised and polyester powder coated die-cast copper-free aluminium body, frosted polycarbonate diffuser, moulded silicone gasket and stainless steel screws. Built-in LED driver 220-240V 50-60Hz, with low-power CREE LED. IP65 rating.



Matt Black (on request)





## Technical data

Wattage	9 WATT	
IP Rating	IP65	
IK Rating	IK08	
Material	High corrosion resistance die-cast copper-free aluminum body	
Coating	Polyester powder coating with phosphocromating pre-finish	
Light source	Low-power CREE LED	
Screws	Stainless steel	
Transformer	Electronic power supply 220/240V 50/60Hz built-in	
Gasket	Silicone rubber	
Rubber grommet	M12 Rutaseal® in EPDM	
Diffuser	Polycarbonate	
Gross weight	1,00 Kg	





light beam options	lumen output (lm)	lumin. efficacy (lm/w)
• 360°	446	49.55
	options	options output (lm)

Anthracite Grey RAL 7016

\* Other light colors available on request: Neutral-white

Finish color options:

Textured Grey RAL 9006

188 | puk.it