



# NANO FULL STAINLESS STEEL

## 8470018

NANO FULL STAINLESS STEEL - 1 LED 3000K 33°

## Lighting information



|                        |              |
|------------------------|--------------|
| Source power type      | 1 LED        |
| Colour temperature     | 3000K        |
| CRI                    | >80          |
| MCADAMS                | 3            |
| LM 80/TM-21            | L80B10@>60Kh |
| Photobiological safety | RG1 @0,7m    |

|              |        |
|--------------|--------|
| Nominal flux | 250 lm |
|--------------|--------|

|                   |             |
|-------------------|-------------|
| Plug-in power     | 2,00 W      |
| Real flux         | 155 lm      |
| Maximum intensity | 2580 cd/klm |
| Beam angle        | 33°         |

|         | Min    | Max    |
|---------|--------|--------|
| Current | 350 mA | 700 mA |
| Power   | 1,00 W | 2,00 W |

|                     |                          |
|---------------------|--------------------------|
| Power Supply Unit   | Max 700mA                |
| Operating frequency | DC                       |
| Dimmable            | PWM                      |
| Safety class        | III                      |
| Wiring              | External                 |
| Cable section       | 2 x 0,50 mm <sup>2</sup> |
| Cable length        | 500 mm;                  |
| Cable type          | PCP rubber               |
| Connector           | To be ordered separately |

|                   |                   |
|-------------------|-------------------|
| Protection Rating | P68 Full Dry (2m) |
| Breaking Strength | IK 07             |
| Walk over         | 500 Kg            |

|                         |                               |
|-------------------------|-------------------------------|
| Energy efficiency class | A/A+/A++                      |
| Diffuser type           | Serigraphed extra-clear glass |
| Diffuser thickness      | 6 mm                          |



## Platek®

PLATEK s.r.l.  
Via Paderno, 19 | 25050 Rodengo Saiano (BS) ITALY  
P.IVA 03320290178 | Codice fiscale 03007130176  
Registro delle Imprese di Brescia n. 03007130176 REA 311057  
Capitale sociale Euro 1.000.000,00 i.v. Società con unico socio

Last update:09/02/2022



# NANO FULL STAINLESS STEEL


## 8470018

NANO FULL STAINLESS STEEL - 1 LED 3000K 33°


## Product features

Body and front locking trim in AISI 316L stainless steel. IP68 Degree of protection with Full Dry system which avoids condensation inside the product. The Installation of the recessed housing in cast concrete with a 20-30 cm gravel soakaway. Only an IP68 connection to the power supply can guarantee the same protection to the fixture. Outer housing and connector to be ordered separately.

## Technical dimensions



## Lighting information



|                   |             |
|-------------------|-------------|
| Plug-in power     | 2,00 W      |
| Real flux         | 155 lm      |
| Maximum intensity | 2580 cd/klm |
| Beam angle        | 33°         |

|                   |             |
|-------------------|-------------|
| Plug-in power     | 2,00 W      |
| Real flux         | 155 lm      |
| Maximum intensity | 2580 cd/klm |
| Beam angle        | 33°         |

## Technical shipping information

|                  |           |
|------------------|-----------|
| Net weight       | 0,30 kg   |
| Gross weight     | 0,40 kg   |
| Packaging width  | 145,00 mm |
| Packaging height | 100,00 mm |
| Packaging depth  | 70,00 mm  |

**Platek®**

PLATEK s.r.l.  
Via Paderno, 19 | 25050 Rodengo Saiano (BS) ITALY  
P.IVA 03320290178 | Codice fiscale 03007130176  
Registro delle Imprese di Brescia n. 03007130176 REA 311057  
Capitale sociale Euro 1.000.000,00 i.v. Società con unico socio

Last update:09/02/2022




# NANO FULL STAINLESS STEEL


## 8470018

NANO FULL STAINLESS STEEL - 1 LED 3000K 33°


### Mechanical accessories




8945033  
Recessed box  $\varnothing$  40 mm H. 76 mm



8945034  
Recessed box  $\varnothing$  35 mm H. 200 mm



8945038  
Recessed box H. 115 mm with base  $\varnothing$  120 mm



8945039  
Recessed box IP67 H. 160 mm with base  $\varnothing$  120 mm




# NANO FULL STAINLESS STEEL


## 8470018

NANO FULL STAINLESS STEEL - 1 LED 3000K 33°


## Electrical accessories




8917006  
IP68 connector for 2x0,75 mm2 cable




8917013  
IP68 Micro Paguro connector for 2x1,5 mm2 cable



8956090  
IP67 Power supply (700mA - 14W)



8956116  
Dimmable driver for maximum 3 luminaires (250mA) (250/700mA - 30/40W) IP20 1-10V+Push+DALI



8956117  
IP67 Power supply (700mA - 30W)

**Platek®**

PLATEK s.r.l.  
Via Paderno, 19 | 25050 Rodengo Saiano (BS) ITALY  
P.IVA 03320290178 | Codice fiscale 03007130176  
Registro delle Imprese di Brescia n. 03007130176 REA 311057  
Capitale sociale Euro 1.000.000,00 i.v. Società con unico socio

Last update:09/02/2022



# NANO FULL STAINLESS STEEL

## 8470018

NANO FULL STAINLESS STEEL - 1 LED 3000K 33°

**Platek®**

PLATEK s.r.l.  
Via Paderno, 19 | 25050 Rodengo Saiano (BS) ITALY  
P.IVA 03320290178 | Codice fiscale 03007130176  
Registro delle Imprese di Brescia n. 03007130176 REA 311057  
Capitale sociale Euro 1.000.000,00 i.v. Società con unico socio

Last update:09/02/2022