

## Bari MINI DL LED



Modern and universal downlight luminaire of high lighting parameters, based on LED module. Applications: offices, restaurants, hotels, corridors, galleries etc.

**Materials:** Powder painted, white aluminum ring, steel sheet body, transparent tempered glass (SH), reflector made of aluminum with a purity of 99,85%.

**Installation:** Into plaster cardboard and modular ceilings.

**Power:** 230 V

### ELECTRICAL DATA

Light source	LED
Luminaire power	13 W
Number of light sources	1
Light source power	11W
Type of equipment	AC
Voltage rating	220 ... 240 V
Light source included	Yes
Power factor	0.96

### MECHANICAL DATA

Type of installation	For 600x600 ceiling
Housing material	Aluminum

### INFORMATION

Colour	White
Operating temperature range	-15 ... 40 °C
Control	Bez

### CERTIFICATES

Degree of protection (IP)	IP44
Degree of protection (IP) / top/	IP20
Class of protection	I
Light source protection	Yes
CE	Yes
EAC	Yes

### LIGHT DATA

Luminaire's luminous efficiency	100 %
Light colour	White
Color rendering index	80
Light distribution	DI
Class of luminaire	I
Light output degradation	B10
Lumen maintenance	L90
Lifetime	> 56000 h
MacAdam	SDCM 3
Lamp Lumen Maintenance Factor (after 60 000h)	89 %

### OPTICAL DATA

Louver/ shutter	Transparent plastic
Diffuser colour	Transparent
Diffuser material	Transparent glass
Reflector	High gloss


### AVAILABLE VARIANTS

Product code	Luminaire luminous flux [lm]	Luminaire's luminous efficacy [lm/W]	Beam angle [°]	Colour temperature
PX1486580 DO001.1166.830.A000	1400	131	20	3000K
PX1486590 DO001.1166.840.A000	1470	136	20	4000K
PX1486585 DO002.1166.830.A000	1480	131	30	3000K

## AVAILABLE VARIANTS


Product code	Luminaire luminous flux [lm]	Luminaire's luminous efficacy [lm/W]	Beam angle [°]	Colour temperature
PX1486592 DO002.1166.840.A000	1550	136	30	4000K
PX1486587 DO003.1166.830.A000	1480	131	50	3000K
PX1486594 DO003.1166.840.A000	1550	136	50	4000K

## DIMENSIONS



H [mm]	F [mm]	G [mm]
110	120	79

H = Height / Depth | F = Outer diameter | G = Inner diameter



Reflector 20°



