


Flat Slim

312175.004.3.76 | Ceiling and wall luminaires

Ceiling and wall luminaires
4051859389781
LED
D 400, H 70



Decorative round LED surface-mounted luminaire for indoor and outdoor use. Base: pressure die-cast aluminium, powder-coated. Standard Gore™ Protective Vents diaphragm valve to avoid condensation. Diffuser: plastic (polycarbonate), opal, shockproof. Diffuser fastening: bayonet system. Suitable for Ceiling mounting, Wall (surface). Very easy installation thanks to plug & play connection. The large connection compartment on the back for convenient connections is also ideal for through wiring. TouchDim sensor capable. Light and/or presence sensors can be integrated.

Colour

Colour silver metallic

Dimensions

Diameter D 400 mm
Height H 70 mm
Weight 2,68 kg

Lamp

Lamp LED exchangeable
Socket Plug
Colour temperature 4000K
Colour rendering index (CRI) 83
Colour tolerance 3
Rated life 50000 h (L70/B10)
Photobiological safety according to EN 62471 Risk group 1

Lighting technology

Colour temperature 4.000 K
Rated luminous flux 3.250 lm
Glare evaluation UGR (4H 8H) 1 22,6
Beam angle 123°

Electrical

Control gear	AC power, DALI dimmable
Voltage	230 V / 50 - 60 Hz
Luminaires on B10A fuse	65
Luminaires on B16A fuse	104
Luminaires on C10A fuse	65
Luminaires on C16A fuse	104
Inrush current / Inrush current duration	0,17 A
System power	31 W
Luminaire efficacy	105 lm/W

Approbations

Type of protection	IP 65
Protection class	I
Filament test	650°C - 30 seconds
Impact resistance	IK08 (5 Joule)
Safety marks	F-mark
Ambient temperature min.	-20 °C
Ambient temperature max.	30 °C
ULOR	10,3 %
Conformity mark	CE, EAC
CIE Flux Code / CEN Flux Code	42 73 92 90 100
Energieeffizienzklasse 2019/2015	E
Non-maintained power mode	Umgebungstemperatur / temperature ambiente => -20 °C ... + 30 °C