



- Sheet steel body.
- Microprismatic PMMA opal diffuser.
- Mains voltage: 220-240V / 50-60Hz.
- 1-10V, DALI and switch dimming options available upon request.
- Over 110lm/W efficiency.
- Emergency kit system can be integrated.
- Designed for T-Bar ceilings.
- Basic colours: white, black, silver, antracite dark gray and special color options available upon request.
- Electronic Led driver positioned outside of the luminaire and connected with wieland connector.

- DKP metal gövde.
- Mikroprizmatik PMMA opal difüzörlü.
- 220-240V / 50-60Hz enerji girişi.
- 1-10V, DALI ve switch dim seçenekleri bulunmaktadır.
- 110lm/W'ın üzerinde verimlilik.
- Acil aydınlatma kit sistemi uygulanabilir.
- T-Profil tavanlar için tasarlanmıştır.
- Standart renkler: beyaz, siyah, gri, antrasit koyu gri ve isteğe bağlı özel renk seçenekleri mevcuttur.
- Led trafosu armatürün dışında armatüre wieland soket sistemi ile bağlanmaktadır.

Panos Radius / 102.LL.19619

SMD LED	.V1	.V2	.V3
Led Power / Led Gücü	11W	41W	65W
System Power / Sistem Gücü	12W	44W	70W
Lumen Output from Fixture / Armatür Çıkış Lümeni CRI>80	2700K	1071	5082
	3000K	1105	5240
	3500K	1127	5347
	4000K	1150	5456
	5000K	1185	5620
Lenght / Uzunluk (A)	400mm	600mm	800mm
Lenght / Uzunluk (B)	400mm	600mm	800mm
Mains Switch Dim Option / 220V Anahtar Dim Opsiyonu	✓	✓	✓
1-10V Dimming Option / 1-10V Dim Seçeneği	✓	✓	✓
Dali Dimming Option / Dali Dim Seçeneği	✓	✓	✓

Wadge

Takoz

