


# Less is more 21

312234.002.1 | LED linear systems



Ceiling and wall luminaires  
4051859235132  
LED  
L 1208, B 42, H 85



Minimalist ceiling and wall luminaire with light emission on three sides. Housing: extruded aluminium profile, anodised or powder-coated. End cap anodised aluminium or powder-coated. Diffuser made of non-yellowing plastic (PMMA), opal. Suitable for Ceiling mounting, Wall (surface). Converter integrated in the canopy.

## Colour

Colour white

## Dimensions

Length L 1.208 mm  
Width B 42 mm  
Height H 85 mm  
Weight 1,29 kg

## Lamp

Lamp LED  
Colour temperature 4000K  
Colour rendering index (CRI) 80  
Colour tolerance 3  
Rated life 60000 h (L80/B10)  
Photobiological safety according to EN 62471 Risk group 1

## Lighting technology

Colour temperature 4.000 K  
Rated luminous flux 2.050 lm  
Glare evaluation UGR (4H 8H) 1 25,4  
Beam angle 180° / 115°

## Electrical

Control gear	Constant voltage supply
Voltage	220 - 240 V / 50 - 60 Hz
Luminaires on B10A fuse	14
Luminaires on B16A fuse	22
Luminaires on C10A fuse	23
Luminaires on C16A fuse	37
Inrush current / Inrush current duration	23.5 A / 240 µs
System power	20 W
Luminaire efficacy	103 lm/W
Power factor	0,5

## Approbations

Type of protection	IP 20
Protection class	I
Filament test	650°C - 30 seconds
Test marks	ENEC, VDE
Safety marks	F-mark
ULOR	28 %
Conformity mark	CE, EAC
CIE Flux Code / CEN Flux Code	33 62 84 72 100
Energieeffizienzklasse 2019/2015	E