

4913.00X

QUALITY MARKS



COLOURS



**ALFA**

**Indoor and outdoor luminaire constructed of:**





- Painted die-cast aluminium body
- Opal polycarbonate or satin glass diffuser
- EPDM gasket
- Stainless steel screws
- Painting using high resistance to UV and corrosion polyester powders

**NOTES**

Luminaires are supplied with a glass diffuser. Available also with polycarbonate diffuser on request.

Code	Light source	Power	Lum. Flux *	Socket	Colour Temperature	Notes
4913.00X	A60	75W		E27		
4913.96X	TC-D	18W		G24 d-2		
4913.66X	LED	13W	1790 lm		4000 K	Built-in electronic power supplier
4913.67X	LED	13W	1790 lm		3000 K	Built-in electronic power supplier

\* Lumen rating is related to the flux emitted by the LED module and not to the flux emitted by the appliance

	Wall mounting		Ceiling mounting		Single power supply cables input		<p>LED : LED's direct operation at 230/240V 50/60Hz. No power supply is required.</p>
<div style="border: 1px solid black; padding: 5px; text-align: center;"><b>IK 04</b></div>	Glass diffuser Impact Energy (J): 0,5	<div style="border: 1px solid black; padding: 5px; text-align: center;"><b>IK 07</b></div>	Polycarbonate diffuser Impact Energy (J): 2				