



# Rounded Midi

582005.0031.1.19 | Ceiling and wall luminaires

Ceiling and wall luminaires  
4051859495956  
LED  
D 268, H 70



Round ceiling and wall luminaire with elegant appearance for outdoor use. Base and housing made of corrosion resistant pressure die-cast aluminium, seawater resistant powder-coated. With membrane valve as a standard to avoid condensed water. Diffuser made of opal plastic (polycarbonate); with diffuser fixing. Base fixing slots outside of gasketed area, drill hole deviations can be compensated. Screwless cover fixing via bayonet lock with safety catch. Includes 1 anti-theft device. With integrated HF movement sensor and light sensor. Mains connection 2 x 3 x 1.5 mm<sup>2</sup>. Second cable inlet for loop through.

## Colour

Colour anthracite metallic

## Dimensions

Diameter D 268 mm  
Height H 70 mm  
Weight 1,55 kg

## Lamp

Lamp 1 LED  
Colour temperature lamp 1 3000K  
Colour rendering index (CRI) 1 80  
Colour consistency (McAdam) 1 3  
Lifetime of lamp 1 combined 40000 h (L70/B50)  
Photobiological safety according to EN 62471 Risk group 1

## Lighting technology

Colour temperature 3.000 K  
Rated luminous flux 370 lm  
Glare evaluation UGR (4H 8H) 1 20,2  
Beam angle 114°

## Electrical

Control gear Converter not necessary  
Voltage 220 - 240 V / 50 Hz  
System power 10 W  
Luminaire efficacy 37 lm/W

## Approbations

Type of Protection IP 66  
Protection Class I  
Glow Wire Test 850°C - 30 seconds  
Impact Protection IK10 (20 Joule)  
Safety marks F-mark  
Ambient temperature min. -20 °C  
Ambient temperature max. 41 °C  
ULOR 1,8 %  
Trade mark CE  
CIE Flux Code / CEN Flux Code 45 76 94 98 100  
Energy efficiency class LED A++  
Energy class of included lamp A++

## Accessories

982410.003 Theft protection  
L 13, B 11, H 16