


Lavano Uno

451199.000 | Ceiling and wall luminaires



Ceiling and wall luminaires
4051859173588
LED
L 1140, B 40, H 83



Linear LED surface-mounted luminaire in an elegant design. Extruded aluminium profile base, lacquered. End caps aluminium, painted. Diffuser: plastic, opal, allows for brilliant glittering light along the lines of the ellipse. Suitable for Ceiling mounting, Wall (surface).

Colour

Colour white aluminium

Dimensions

Length L 1.140 mm
Width B 40 mm
Height H 83 mm
Weight 2,25 kg

Lamp

Lamp LED
Colour temperature 3000K
Colour rendering index (CRI) 80
Colour tolerance 3
Rated life 50000 h (L90/B10)
Photobiological safety according to EN 62471 Risk group 1

Lighting technology

Colour temperature 3.000 K
Rated luminous flux 2.500 lm
Glare evaluation UGR (4H 8H) 1 24,7
Beam angle 146° / 108°

Electrical

Control gear	Converter
Voltage	220 - 240 V / 50 - 60 Hz
Luminaires on B10A fuse	8
Luminaires on B16A fuse	13
Luminaires on C10A fuse	27
Luminaires on C16A fuse	43
Inrush current / Inrush current duration	20 A / 200 μs
Ripple current / Flicker	4 %
System power	23 W
Luminaire efficacy	109 lm/W
Total harmonic distortion	10 %
Power factor	0,97

Approbations

Type of protection	IP 40
Note: Type of Protection	IP 40
Protection class	I
Filament test	650°C - 30 seconds
Impact resistance	IK02 (0,20 Joule)
Safety marks	F-mark
ULOR	22,7 %
Conformity mark	CE, EAC
CIE Flux Code / CEN Flux Code	36 62 83 77 100
Energieeffizienzklasse 2019/2015	E