



NETTUNO Bronze Floodlight

8472318

NETTUNO Bronze Floodlight - 9 LED 3000K 45°

Lighting information

Source power type	9 LED
Colour temperature	3000K
CRI	>80
MCADAMS	3
LM 80/TM-21	L80B10@>60Kh

Source power	14,50 W
Nominal flux	1710 lm

Plug-in power	15,00 W
Real flux	1140 lm
Maximum intensity	1585 cd/klm
Beam angle	45°

Power Supply Unit	24V
Operating frequency	DC
Dimmable	Not dimmable
Safety class	III
Wiring	External
Cable section	2 x 2,50 mm ²
Cable length	5.000 mm;
Cable type	H07RN-F
Connector	To be ordered separately

Protection Rating	IP68 Full Dry (2m)
Breaking Strength	IK 06

Energy efficiency class	A/A+/A++
Diffuser type	Transparent extra-clear glass
Diffuser thickness	5 mm



Platek®

PLATEK s.r.l.
Via Paderno, 19 | 25050 Rodengo Saiano (BS) ITALY
P.IVA 03320290178 | Codice fiscale 03007130176
Registro delle Imprese di Brescia n. 03007130176 REA 311057
Capitale sociale Euro 1.000.000,00 i.v. Società con unico socio


Last update:04/02/2022

NETTUNO Bronze Floodlight

Product features

Body and front locking trim manufactured in bronze casting. This has superior resistance against corrosion in aggressive saline environments that are superior to the industry standards. A4 Stainless steel screws. IP68 Degree of protection with Full Dry system which avoids condensing inside the product.

Technical dimensions




Technical shipping information

Net weight	5,20 kg
Gross weight	5,50 kg
Packaging width	260,00 mm
Packaging height	260,00 mm
Packaging depth	260,00 mm

8472318


NETTUNO Bronze Floodlight - 9 LED 3000K 45°

Lighting information



Plug-in power	15,00 W
Real flux	1140 lm
Maximum intensity	1585 cd/klm
Beam angle	45°

Lighting Simulation



Wide beam angle

simulation made with NETTUNO Bronze Floodlight 15,0 W 3000K

Optics:	45°
Code:	8472318
Distance from wall:	6 m
Distance between products:	5 m
Wall height:	6 m

Plug-in power	15,00 W
Real flux	1140 lm
Maximum intensity	1585 cd/klm
Beam angle	45°

Platek®

PLATEK s.r.l.
Via Paderno, 19 | 25050 Rodengo Saiano (BS) ITALY
P.IVA 03320290178 | Codice fiscale 03007130176
Registro delle Imprese di Brescia n. 03007130176 REA 311057
Capitale sociale Euro 1.000.000,00 i.v. Società con unico socio

Last update:04/02/2022

NETTUNO Bronze Floodlight


8472318

NETTUNO Bronze Floodlight - 9 LED 3000K 45°


Electrical accessories



8917004
IP68 IN/OUT connector for 3x4 mm² cable



8956127
IP67 Power supply (24V DC - 75W)



8956307
IP20 Power supply (24V DC - 75W)



8956313
Power supply DALI (24V DC - 120W) IP67



NETTUNO Bronze Floodlight

8472318

NETTUNO Bronze Floodlight - 9 LED 3000K 45°

The gluing process and plasma treatment

One of the most complex and delicate aspects in outdoor lighting products is the fitting of glass onto the lighting body. This must ensure over time an excellent degree of insulation from atmospheric agents, even in harsh environmental conditions, to maintain a stable performance with zero maintenance. The gluing process of the glass on Platek products is managed at an automated workstation, preceded by a pre-treatment of the surfaces with atmospheric pressure plasma. Pre-treatment modifies the characteristics and ionic properties of the treated surfaces, activates the polar materials at strategic points, removes any residue of detaching agents, such as silicones and oils with a precision microcleaning, favouring excellent wettability of the bonded surfaces and a stable seal in time. The gluing process of the glass with specific plasma treatment allows a bonding force four times greater than similar products to be obtained. The shaping of the surfaces is followed by the application of the silicone and the assembly of the glass onto the lighting body using an automated process that guarantees perfect sealing of the lamp.

Precise LED selection

All LEDS used by Platek, once assembled by trusted personnel are tested with suitable instruments to check the colour specification required by Platek standards. The choice of using only 3 McAdams colour steps and with a CRI value exceeding 90, provide a high level of light quality that is difficult to find in the world of outdoor lighting. As far as LED products are concerned, Platek has adopted a system of protection against electrostatic discharge along the entire production chain of electronic components to increase the resistance of circuits to power surges.

Platek®

PLATEK s.r.l.
Via Paderno, 19 | 25050 Rodengo Saiano (BS) ITALY
P.IVA 03320290178 | Codice fiscale 03007130176
Registro delle Imprese di Brescia n. 03007130176 REA 311057
Capitale sociale Euro 1.000.000,00 i.v. Società con unico socio

Last update:04/02/2022